

Product Data Sheet

EXPOSE-IT! FC

Surface Retarders

Description: Expose It! FC is a water-based retarder for exposed aggregate concrete. Expose It! FC is an easy-to-use and economical method for producing exposed aggregate concrete with consistent results. This materials thicker viscosity makes it ideal for face up ribbed panels where a thin or runny retarder would not be tolerated.

Advantage:

- Easy to use.
- Costs just pennies per square foot.
- Environmentally safe, water based formulation.
- Color-coded blue for ease of application.

Preparation: Mix material thoroughly before using.

Application: As soon as surface water dissipates (usually within about 15 minutes), apply Expose It! FC at a rate of 150 – 200 square feet per gallon with paint sprayer. Apply material so it hides the areas to be exposed.

Wash Off: Wash off with high-pressure sprayer the next day or in some cases, later the same day if high temperatures are present (consult with a Fister technical rep before wash off on the same day).

Coverage: 150 – 200 square feet per gallon.

Clean Up: Clean sprayers with soap and water.

Storage: Do not store in metal sprayers for a prolonged time.

Packaging: 5 gallon pails, 55 gallon drums and 275 gallon totes.

Precaution: Remove retarded concrete no later than one day after product is sprayed on concrete. Variations depend on temperature, P.S.I. of concrete and water to cement ratio.