

**FISTER, INC.**

1150 LYON ROAD  
BATAVIA, IL 60510  
630/761-0100  
630-761-0108 FAX  
800/542-7393

**Product Data Sheet****EXPOSE-IT! FC****Surface Retarder**

**Description:** Expose It! FC is a water-based retarder for exposed aggregate concrete. Expose It! FC is an easy-to-use and economical method for producing exposed aggregate concrete with consistent results. This materials thicker viscosity makes it ideal for face up ribbed panels where a thin or runny retarder would not be tolerated. Because of its thicker viscosity, Expose It FC is excellent for use on Brick Faced panel projects.

**Advantage:**

- Easy to use.
- Costs just pennies per square foot.
- Environmentally safe, water based formulation.
- Color-coded blue for ease of application.

**Preparation:** Mix material thoroughly before using.

When used as an exposed aggregate retarder:

**Application:** As soon as surface water dissipates (usually within about 15 minutes), apply Expose It! FC at a rate of 150 – 200 square feet per gallon with paint sprayer. Apply material so it hides the areas to be exposed.

**Wash Off:** Wash off with high-pressure sprayer the next day or in some cases, later the same day if high temperatures are present (consult with a Fister technical rep before wash off on the same day).

**Coverage:** 75 – 100 square feet per gallon.

**Clean Up:** Clean sprayers with soap and water.

**Storage:** Do not store in metal sprayers for a prolonged time.

**Packaging:** 5 gallon pails, 55 gallon drums and 275 gallon totes.

**Precaution:** Remove retarded concrete no later than one day after product is sprayed on concrete. Variations depend on temperature, P.S.I. of concrete and water to cement ratio.

When used as a product for Brick Faced projects:

**Preparation:** Mix thoroughly before using.

**Application:** Spray, Brush or roll on Expose It FC to bricks prior to putting them in a form liner.

**Wash off:** Wash off with high pressure sprayer the next day leaving bricks clean without cement paste on them.