

FISTER, INC.

1150 LYON ROAD
BATAVIA, IL 60510
630/761-0100
630-761-0108 FAX
800/542-7393

FORM SEAL

Product Data Sheet

Moisture cure urethane

Protective coating for wood and concrete forms.

Description: Form Seal is a high performance one-component cure urethane that is ideally suited to coat porous wood or concrete formwork. This abrasion and chemically resistant material forms a tough waterproof film that will preserve the life of wood and concrete forms.

Surface Preparation: All surfaces must be clean and dry before application.

Concrete: Prior to application of Form *Seal*, prepare surface with light dust blast or by acid wash. Rinse thoroughly and allow to dry.

Wood: Sand rough wood to a smooth surface. If wood grain rises after the first coat, sand lightly before applying a second coat.

Application Instructions: Apply Form Seal by brush or roller. Two coats are recommended for maximum protection.

First Coat: On concrete, thin first coat one to one with solvent (xylene or toluene). On wood, thinning is not necessary. Allow first coat to cure (typically 2-4 hours).

Second Coat: For both wood and concrete, apply material directly from container, no thinning is needed. Do not wait more than 24 hours to recoat, as the first coat will become so hard it will not allow a second coat to stick.

Coverage: 300-400 sq. ft. per gallon

Clean up: Clean all equipment with solvent (xylene, toluene or acetone) immediately after use.

Packaging: Available in 5-gallon pails

Storage: Store indoors at room temperature

Caution: Withdraw only the amount of material you intend to use. Close container immediately to prevent contact with air. Do not pour unused material into container. Store unused material separately and use within 24 hours.