

**FISTER, INC.**  
1150 LYON ROAD  
BATAVIA, IL 60510  
630/761-0100  
630-761-0108 FAX  
800/542-7393

## **EXPOSE-IT!**

### **MOLD RELEASE**

**EXPOSE-IT! RELEASE** is a transfer agent used under retarder to help reduce form cleaning after stripping of concrete.

#### **Description**

Apply this *one-coat* material prior to application of EXPOSE-IT! Form Retarder to reduce clean up time of forms, leaving them ready for the next cast.

#### **Advantages:**

- ❖ Allows casting immediately after stripping
- ❖ Reduces clean-up
- ❖ Prevents pull-outs or uneven edges
- ❖ Costs just pennies per square foot

#### **Surface Preparation**

Forms must be clean, dry and non-porous. Seal porous forms with Armorgard 505 products or Form Seal.

#### **Mixing**

Mix material prior to use. This can be accomplished by mechanically or manually shaking and/or rolling containers.

#### **Application**

Apply by spray, brush or roller. Dry time is dependent on ambient temperature (usually a few minutes is all that is needed). Apply EXPOSE-IT! Form Retarder when material is completely dry.

#### **Clean Up**

Clean tools and equipment with soap and water. Clean skin immediately with soap and water or industrial hand cleaner.

#### **Packaging and Coverage**

300-400 square feet per gallon.

EXPOSE-IT! Mold Release is packaged in 5-gallon pails with 55-gallon drum packaging available upon request.

#### **VOC**

750 g/l

#### **Fire/Flammability**

Highly Flammable

#### **Disposal**

Refer to SDS

#### **Storage**

Store in cool dry area

#### **Warning**

This is not a release agent. It is to be used exclusively under EXPOSE-IT! Form Retarder to aid in the transfer of that material. Make sure material is completely dry prior to application of EXPOSE-IT Form Retarder.